

**Mechanical Data**

- Surface Mount Package
- Case Material: Molded Plastic, UL Flammability Rating 94V-0
- Terminals: Finish - Matte Tin Plated Leads, Solderable per MIL-STD-202, Method 208 (e3)
- Polarity: Cathode Bar
- Weight: 0.064 grams (Approximate)
- Max Soldering Temperature 260°C for 30secs as per JEDEC J-STD-020


**Package View**



Top View

**Package Outline Dimensions**


SMAF



SMAF		
Dim	Min	Max
A	0.90	1.10
b	1.25	1.65
c	0.10	0.40
D	2.25	2.95
E	3.95	4.60
HE	4.80	5.60
L	0.50	1.50
All Dimensions in mm		

**Suggested Pad Layout**

SMAF



Dimensions	Value (in mm)
C	4.00
G	1.50
X	2.50
X1	6.50
Y	1.70

**Note:** The suggested land pattern dimensions have been provided for reference only, as actual pad layouts may vary depending on application. These dimensions may be modified based on user equipment capability or fabrication criteria. A more robust pattern may be desired for wave soldering and is calculated by adding 0.2 mm to the 'Z' dimension. For further information, please reference document IPC-7351A, Naming Convention for Standard SMT Land Patterns, and for International grid details, please see document IEC, Publication 97.

**Note:** For high voltage applications, the appropriate industry sector guidelines should be considered with regards to creepage and clearance distances between device Terminals and PCB tracking.

**Minimum Packing Quantity**

	Quantity	Tape Width	Part Number Suffix
13" Reel	10,000	12mm	-13

**Note:** Package quantities given are for minimum packaging quantity only, not minimum order quantity. For minimum order quantity, please contact Sales Department.

**Note:** No mixed date codes or partial quantity (less than minimum packaging quantity) per packaging is allowed.

**Note:** In no case shall there be two or more consecutive components missing from any reel for any reason.


**Device Tape Orientation**

Tape Width	Part Number Suffix	Tape Orientation
12mm	-13	

**Note:** For part marking, refer to product datasheet.



**Note:** Tape and package drawings are not to scale and are shown for device tape orientation only.

**Embossed Carrier Tape Specifications**



Tape Width (W)	Dimension	Value (mm)	Dimension	Value (mm)	Dimension	Value (mm)
12mm	<b>Ao</b>	3.0±0.10	<b>E</b>	1.75±0.10	<b>P0</b>	4.0±0.05
	<b>Bo</b>	5.6±0.10	<b>F</b>	5.5±0.05	<b>P1</b>	2.0±0.05
	<b>D</b>	1.5±0.10	<b>K</b>	1.2±0.10	<b>t</b>	0.25 ±0.05.
	<b>D1</b>	1.5 min.	<b>P</b>	4.0±0.10	<b>W</b>	12±0.20
	<b>A0 B0 K0</b>	Determined by component size. The clearance between the component and the cavity must comply to the rotational and lateral movement requirement provided in figures in the "Maximum Component Movement in Tape Pocket" section.				

**Embossed Carrier Tape Specifications** (Continued)




---


## Maximum Component Movement in Tape Pocket

---


### Component Lateral Movement



### Maximum Component Rotation




**Surface Mount Reel Specifications**



Tape Width	Reel Size	A (mm)	B* (mm)	C (mm)	D* (mm)	N (mm)	G (mm)	T (mm)
12mm	13"	330 ±2	2.0 +0.5 -0	13 ±1	20.5 ±0.2	50 (min)	14.4 (max)	18.4 (max)

**Tape Leader and Trailer Specifications**



**Note:** There shall be a leader of at least 230mm which may consist of carrier tape and/or cover tape or a start tape followed by at least 160mm of empty carrier tape sealed with cover tape.

**Note:** There shall be a trailer of at least 160mm of empty carrier tape sealed with cover tape. The entire carrier tape must release from the reel hub as the last portion of the tape unwinds from the reel without damage to the carrier tape and the remaining components in the cavities.