


Package Outline Dimensions

X4-DSN0607-3 (Type B)




X4-DSN0607-3 (Type B)			
Dim	Min	Max	Typ
A	0.20	0.26	0.225
A1	0.022	0.028	0.025
A2	0.18	0.23	0.20
b	0.24	0.26	0.25
b1	0.14	0.16	0.15
D	0.56	0.64	0.60
E	0.66	0.74	0.70
e	--	--	0.40
e1	--	--	0.35
k	--	--	0.225
k1	--	--	0.175
L	0.49	0.51	0.50
La	0.14	0.16	0.15

All Dimensions in mm

Suggested Pad Layout

X4-DSN0607-3 (Type B)



Dimensions	Value (in mm)
C	0.40
C1	0.35
X	0.15
X1	0.25
Y	0.15
Y1	0.50

ALL DIMENSIONS ARE NOMINAL VALUES SHOWN IN MILLIMETERS

Note: The suggested land pattern dimensions have been provided for reference only, as actual pad layouts may vary depending on application. These numbers may be modified based on user equipment capability or fabrication criteria. A more robust pattern may be desired for wave soldering and is calculated by adding 0.2 mm to the 'Z' dimension. For further information, please reference document IPC-7351A, Naming Convention for Standard SMT Land Patterns, and for International grid details, please see document IEC, Publication 97.